



Independent disc stubble cultivators
OPTIMER L 6000 - 7500

PRODUCT INFORMATION




OPTIMER L : The advantage of stubble cultivations

Take advantage of the unbeatable working quality of the new range of KUHN independent disc cultivators. These new machines, with their outstanding throughput capacity and optimum operating comfort, will assist you with all of your stubble cultivation requirements.

OPTIMER L

6000-7500



Agronomic benefits

- Large under-frame clearance offering good quality cutting and mixing in the first pass even in the presence of abundant vegetation.
- Mechanical destruction of weeds, crop regrowth or other vegetation cover.
- Creation of fine soil favourable to germination for stale seedbed creation or before planting a crop.

Ground following

- Active ground pressure management with STEADY CONTROL technology.
- Constant pressure in the extension cylinders ensures homogeneous work on all your fields, even hilly ones.
- Fuel-saving system with perfect control of the working depth.

Options to meet all requirements

- Levelling board levels the ploughing and breaks up clods on the surface.
- Chopping roller helps with soil flow in the presence of abundant residues and accelerates their decomposition for better mineralization.
- Small notched discs guarantee a good mixing in surface cultivations.
- Large notched discs allow an efficient uprooting up to 10 cm deep.

Technical specifications

Models	6000	7500
Minimum tractor power (kw/hp)	133 / 180	166 / 225
Maximum tractor power (kw/hp)	221 / 300	265 / 360
Working width (m)	6	7.5
Transport width (m)	3	3
Working depth (cm)	3 to 10	
Working depth adjustment	Hydraulic assistance with lower stop	
Diameter/thickness of serrated discs (mm)	510 / 6	
Transport wheel size	550 / 55 x 22.5	
Number of discs	48	60
Hitch options	3/4/4N cross-shaft - K 80 ball hitch - Ring hitch	
Weight (kg) with double roller U	5600	6200
Type of roller available	Double U / HD-Liner	

KUHN-HUARD S.A.S. - 2, rue du Québec - Zone Horizon - 44110 Châteaubriant France - www.kuhn.com

Information given in this document is only for information purposes and is non-contractual. Our machines are in compliance with regulations in force in the country of delivery. In our literature, and for improved illustration of certain details, some safety devices may not be in operating position. When operating these machines, these devices must be in position in accordance with the requirements indicated in the operator's manuals and assembly manuals. Respect the tractor gross vehicle weight rating, its lift capacity and maximum load per axle and tyres. The tractor front axle load must always comply with the regulations of the country of delivery (In Europe, it must reach minimum 20 % of the tractor net weight). We reserve the right to change any designs, specifications or materials listed without further notice. Machines and equipment in this document can be covered by at least one patent and/or registered design. Trademarks cited in this document may be registered in one or several countries.

To protect the environment, this leaflet is printed on chlorine-free paper. Printed in France - 950 081 GB - 01.21 - Copyright KUHN 2021

