

Topper 9

Heavy Duty Set-a-Side Mower - Cutting Width 2.75m (9')



Machine Features

- » 2.75m (9' 0") cutting width
- » Three-point linkage-mounting
- » Pasture and set-a-side mower
- » Heavy-duty build quality
- » All shaft drive
- » Hardened updraft, swinging blades
- » Opposing rotors with 85mm blade overlap
- » 540rpm PTO
- » Slip clutch protection
- » Front and rear chain guards
- » 2 x 360 degree swivel tailwheels
- » Puncture proof tyre
- » Replaceable full length skids
- » Cutting heights from 25mm to 300mm
- » Maximum cutting diameter 50mm
- » UK's best selling 9ft topper

Markets

- » Agricultural
- » Contractors

Tractor Requirements

- » 50hp minimum tractor horse-power (dependent on model)
- » Three-point linkage-mounting



» Transport



» Pasture Mowing

Description		Topper 9
Cutting width	Maximum width of cut (m)	2.75 (9' 0")
HP requirement	Minimum hp requirement of tractor	50
Weight	Weight of machine (kg)	950
Attachment	3-Point Linkage	3-Point Linkage
Cutting height	Minimum to maximum cutting height (mm)	25 - 300
Cutting capacity	Maximum diameter of material to be cut (mm)	50
Overall width	Maximum external width (m)	3
PTO speed	Maximum RPM of PTO shaft	540
Protection	Provides protection to both mower and tractor	Shear bolt
Blade carriers	Number of carriers on mower	2
Number of rotors	The number of rotors per mower	2
Blade tip speed	Measured in meters per min	4140m per min
Blade overlap (mm)	Distance blades overlap when running (mm)	85
Wheels	Number of wheels	2
Skids	Number of skid shoes per mower	2