

Strip Till

STRIGER 100

Product information



www.kuhn.com



Invest in the row with STRIGER 100. Get exceptional output quality from this strip till tool with its easy settings that allow quick adaptation to all of your operations.



COMFORT AND PRECISION

- **Tool-free adjustment** of trash removers
- **Tool-free tine adjustment**
- **Hydraulic adjustment** of tamping wheel



PERFECT GROUND FOLLOWING

- **Trapezium-mounted**
- Gauge wheel in optimum position for cutting residues



NEW TINE

- Quick-change point
- Lower pull-power requirement
- Fully protected leg



HIGHLY ADAPTABLE

- Manure, liquid or solid fertilisers
- Different inter-row widths
- Two types of deflector disc
- Two types of opening disc
- Discs for springtime operations



HIGH QUALITY FINISH

- Wire wheel : for fine soil
- Chain wheel : for better water infiltration
- Rubber wheel : for moisture retention



SAFETY IN STONY GROUND

- NSH tine safety up to 1,000kg
- Opening discs, trash removers and side deflectors with NSM safety system

Technical specifications

STRIGER

| Models | 300 | | | 440 R | | | 600 R | | | |
|---------------------------------------|--|-------|-------|--|-------|-------|----------|-------|----|-------|
| Chassis (m) | 3.00 | | | 4.40 | | | 6.00 | | | |
| Number of rows | 4 | 5 | 6 | 6 | 7 | 8 | 8 | 9 | 11 | 12 |
| Spacing (cm) | 60-70-75-80 | 55-60 | 45-50 | 70-75-80 | 55-60 | 45-50 | 70-75-80 | 55-60 | 55 | 45-50 |
| Transport width(m) | 3.00 | | | | | | | | | |
| Power requirement | Between 20hp and 35hp per row | | | | | | | | | |
| Working depth (cm) | From 7 to 30cm | | | | | | | | | |
| Linkage | Cat 2 - 3 | | | Cat 3 - 4N - Quick Hitch 4N | | | | | | |
| Necessary tractor hydraulic equipment | NSH and tamping wheel : 1 DA Trapezium : 1 DA | | | NSH and tamping wheel : 1 DA Trapezium : 1 DA Folding + locking : 1 DA | | | | | | |



KUHN Huard S.A.

2, rue du Québec - Zone Horizon - 44110 CHATEAUBRIANT

In European Union countries, our material is conform to the European "Machines" Directive ; in other countries, it is in compliance with current safety regulations. In our prospectuses, for a clearer illustration of details, some safety systems have been removed. It is imperative that these safety systems be left in place in all circumstances, in compliance with the instructions notice. "We reserve the right to modify, without notice, our models, equipment and accessories". The machines and equipment on this document may be patented and/or have a registered design. The brands cited in this document may be protected in one or several countries.

Check
KUHN out on
www.kuhn.com

