

CY2000

Rotary Mower - Cutting Width 2.0m (6' 7")



Machine Features

- » 2.0m (6' 7") cutting width
- » Heavy duty 'push-bar' as standard
- » 1000rpm PTO shaft
- » 8mm steel deck
- » Three-point linkage mounting
- » Heavy-duty chain guard
- » Floating linkage for close cut
- » Heavy duty construction
- » Heavy-duty 7kg axe-style cutting
- » Four-plate slip clutch protection



Scrub Maintenance



7kg heavy-duty blades

Markets

- » Forestry
- » Governmental
- » Contractor
- » Agricultural

Tractor Requirements

- » 100hp minimum tractor horse power (dependent on model)
- » Three-point linkage-mounting

Description		CY2000
Cutting width	Maximum width of cut (meters)	2.0 (6' 7")
HP requirement	Minimum hp requirement of tractor	100
Weight	Weight of machine (kg)	1400
Attachment	Type of linkage to tractor	3-Point Linkage
Cutting height	Minimum to maximum cutting height (mm)	25 - 225
Cutting capacity	Maximum diameter of material to be cut (mm)	75
Overall width	Maximum external width (m)	2.12
Overall length	Maximum external length (m)	2.84
PTO speed	Maximum RPM of PTO shaft	1000
Gearbox rating	Rotor gearbox (hp)	150
Protection	Provides protection to both mower and tractor	Slip clutch
Blade carriers	The number of rotors	1
Number of blades	Number of heat treated updraft blades	3
Blade tip speed	Wings (measured in m per min)	4950