

PT Series

Pasture Topper - Cutting Width 1.8m (5' 11"), 2.4m (7' 11"), 2.75m (9')



Machine Features

- » 1.8m, 2.4m and 2.7m cutting widths
- » Three-point linkage mounting
- » Offset model available
- » Low tractor horsepower requirement
- » Easily adjustable cutting heights
- » Quick and easy mounting
- » PTO overrun protection
- » 540 rpm PTO drive
- » Cutting heights from 24mm to 114mm
- » Maximum cutting diameter 30mm



PT180



PT240 Offset

Markets

- » Agricultural

Tractor Requirements

- » 35hp minimum tractor horsepower (dependent on model)
- » Three-point linkage-mounting

Description		PT180	PT270	PT240 Offset
Cutting width	Maximum width of cut (m)	1.8 (5' 11")	2.75 (9')	2.4 (7' 11")
HP requirement	Hp requirement of tractor	30-70	45-80	45-80
Weight	Weight of machine (kg)	500	565	565
Attachment	3-Point Linkage	3-Point Linkage	3-Point Linkage	3-Point Linkage
Cutting height	Min - max cutting height (mm)	24 - 114	24 - 114	24 - 114
Cutting capacity	Max diameter to be cut (mm)	30	30	30
Overall width	Maximum external width (m)	2.0	2.94	2.6
PTO speed	Maximum RPM of PTO shaft	540	540	540
Protection	Protection to both mower and tractor	Shear Bolt	Shear Bolt	Shear Bolt
Blade carriers	Number of carriers on mower	1	2	2
Number of rotors	The number of rotors per mower	1	2	2
Blade tip speed	Wings (measured in m per min)	4500m per min	4620m per min	4620m per min
Blade overlap	Distance blades overlap when running (mm)	N/A	50	50
Skids	Number of skid shoes per mower	2	2	2